



» PRODUCT BULLETIN

Cesa™ Fiber Tracer Concentrates

The textile supply chain is usually long and complex, with several material and service suppliers playing a role. This can make it difficult to trace a garment or other type of fabric product back to the fiber manufacturer and brand owner. Cesa™ Fiber Tracer Concentrates are polymer solutions that include a taggant, unique to the customer/product line, which is incorporated into the fibers during the spin-dyeing process. A test carried out on the textile can confirm the presence of the unique taggant and therefore confirm the customer/product line the textile originated from. Fiber producers can also add the tracer concentrate to shredded waste polyester and polyamide, and convert them together into polymer pellets. Cesa Fiber Tracer Concentrates contain no hazardous raw materials and comply with key fiber regulations.

APPLICATIONS

Cesa Fiber Tracer Concentrates are particularly recommended for apparel, sportswear, and home textiles to support brand ownership and labels such as those for recycled content, “made in”, and bio-polymer content.

KEY BENEFITS

- Unique and personalized tracer for customer/product lines
- Suitable for polyester and polyamide (nylon), including recycled grades; possibility to develop solutions for bio-polymers
- No impact on spinnability, color or yarn properties
- Can be combined with color into a single product for convenience
- Complies with key regulatory requirements by EN, DIN, UNI and others
- Supplied with a testing service package





1.844.4AVIENT
www.avient.com



Copyright © 2022, Avient Corporation. Avient makes no representations, guarantees, or warranties of any kind with respect to the information contained in this document about its accuracy, suitability for particular applications, or the results obtained or obtainable using the information. Some of the information arises from laboratory work with small-scale equipment which may not provide a reliable indication of performance or properties obtained or obtainable on larger-scale equipment. Values reported as "typical" or stated without a range do not state minimum or maximum properties; consult your sales representative for property ranges and min/max specifications. Processing conditions can cause material properties to shift from the values stated in the information. Avient makes no warranties or guarantees respecting suitability of either Avient's products or the information for your process or end-use application. You have the responsibility to conduct full-scale end-product performance testing to determine suitability in your application, and you assume all risk and liability arising from your use of the information and/or use or handling of any product. AVIENT MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, either with respect to the information or products reflected by the information. This literature shall NOT operate as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner.